




Exterior Hard Surface Floor Coating

Product Information Side 1

| Picture | Description | | |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------|
|  | <p>With our Vikote Specialty 8010 Floor Repair Compound, cracks, spalls, and holes are quickly and easily remedied. This easy to use compound is perfect for patching failures in interior or exterior applications including cracks, spalls, even sink holes! Not UV stable but completely VOC compliant, this solvent-borne powerhouse is ready to grind in less than an hour. This compound is thick enough to trowel on but thin enough to self level in most applications. Although this compound can be used outdoors it will require an additional topcoat of one of our many uv stable formulations.</p> | | |
| Quick Facts | Standard Performance Data | | |
| Price Per Square Foot | N/A | UV-Stable | No |
| Availability | Out Of Stock | 100% Solids | Yes |
| Processing Time | N/A | No VOC's | Yes |
| Available Containers | Gal; Pail; Drum | No Solvents | Yes |
| Available Colors | N/A | Recoatable | Yes |
| Application Tips | Substrates | | |
| Application Type | Ceramic Tile | | |
| Mix Ratio | 1A:1B Ratio | VCT | Joints |
| Cure Time - Dry to Touch | 3-8 Min | | |
| Cure Time - Recoat Window | 10 Min | | |
| Cure Time - Back to Service | 10 min - 1 hr | | |
| Thickness | 1/4" Max | | |
| Unique Traits | None | | |
| | | Aluminum | Yes |
| | | Concrete | Yes |
| | | OSB | Yes |
| | | Gypsum | Yes |
| | | Asphalt | |
| | | Rubber | |
| | | Quarry Tile | Yes |
| | | Plastic | |
| Pricing | | | |
| | | | |



Exterior Hard Surface Floor Coating

Product Information Side 2

Technical Data

Additional Images

| | |
|----------------------------------------------|----------|
| Tensile Strength | N/A |
| Adhesion (Concrete) | N/A |
| Hardness (ASTM D-2134; Shore D) | N/A |
| Abrasion Resistance (ASTM D4060; CS17 Wheel) | N/A |
| Impact Resistance (ML D-2794) | N/A |
| Elongation (ASTM D-2370) | N/A |
| Hydrostatic Pressure Resistance | N/A |
| Low temp flex test | N/A |
| Vehicle Type | N/A |
| Finish | N/A |
| Percent Solids | N/A |
| Aliphatic/Aromatic | N/A |
| Coefficient of Friction | N/A |
| Cure Rate (RE-Coat) | 30-60min |
| Cure Rate (Back to Service) | N/A |