




Exterior Hard Surface Floor Coating

Product Information Side 1

Picture		Description	
		<p>Just like the entire Vikote Standard family of products, the 9070 series of our pure polyurea coating is made of 100% solids and is 100% uv stable. This coating is designed to allow thicker coats (greater than 10 mils) in a single application on outdoor surfaces. Most commonly used on flooring applications, it provides a durable high gloss, low maintenance finish in a single application. This series has two available variations, one with additional fillers for a thicker formulation and one with enhanced adhesion properties for compatibility with more surfaces.</p>	
Quick Facts		Standard Performance Data	
Price Per Square Foot	\$1.18	UV-Stable	Yes
Availability	In-Stock	100% Solids	Yes
Processing Time	2 Weeks	No VOC's	Yes
Available Containers	Gal; Pail; Drum	No Solvents	Yes
Available Colors	Clear/Standard	Recoatible	Yes
Application Tips		Substrates	
Application Type	Brush; Roll; Squeegee	Ceramic Tile	
Mix Ratio	1A:1B Ratio	VCT	Yes
Cure Time - Dry to Touch	1-4 hrs	Glass	
Cure Time - Recoat Window	Within 5 days	Wood	Yes
Cure Time - Back to Service	2-24 hrs	Steel	Yes
Thickness	Max thickness 50 mils	Stainless Steel	
Unique Traits	None	Fiberglass	
		Aluminum	Yes
		Concrete	Yes
		OSB	Yes
		Gypsum	Yes
		Asphalt	
		Rubber	
		Quarry Tile	Yes
		Plastic	
Pricing			



Exterior Hard Surface Floor Coating

Product Information Side 2

Technical Data			Additional Images
Tensile Strength		2200psi	
Adhesion (Concrete)		1100 psi	
Hardness (ASTM D-2134; Shore D)		55	
Abrasion Resistance (ASTM D4060; CS17 Wheel)		N/A	
Impact Resistance (ML D-2794)		N/A	
Elongation (ASTM D-2370)		200.00%	
Hydrostatic Pressure Resistance		N/A	
Low temp flex test		N/A	
Vehicle Type	Epoxy	Polyurea	
Finish	High Gloss	High Gloss	
Percent Solids	0.4	1	
Aliphatic/Aromatic	0.4	Ali	
Coefficient of Friction		N/A	
Cure Rate (Re-Coat)		15-30 min	
Cure Rate (Back to Service)		8-48 hrs	